



INNOFLUID SOLUTIONS SDN BHD

CONTAINER SELECTION CRITERIA

Innofluid requires that all containers supplied shall be suitable for the safe and legal transport of up to 24,000 litres of non-hazardous bulk liquid in Flexitanks. Containers must be in strict compliance with the following criteria:

1. Container shall be 30 ton rated
2. All 20' ISO dry freight containers shall be Grade A and 5 years of age or less
3. The container shall not have Decal panels
4. All containers supplied shall be manufactured in accordance with all the relevant ISO requirements defining design, testing, identification and markings, corner fittings, dimensions and ratings and operational requirements.
5. Containers shall be supplied in a suitable condition for transport by road, rail or sea.
6. Vertical recess in rear corner post assemblies to accept bulkhead fixing bolts.
7. Two fully operative locking bars on each door.
8. Containers shall be free of any hazardous cargo markings/labels.
9. Any container supplied for the use of the transport of Flexitanks shall be free of any debris, sharp edges, floor splinters, proud or loose floor screws, dent or any such weld or similar repair on the inside surface of the cargo area that may cause damage to the flexitank. All interior surfaces, including the floor surface, shall be free of transferable stains and other sources of contamination that may react with the flexitank material and/or leach into the liquid cargo.
10. Containers shall be lined with cardboard on the entire floor surface the front panel surface up to the height of the fully loaded flexitank, the sidewall panel surfaces up to the height of the fully loaded flexitank.

Innofluid at all times reserves the right to reject damages containers or those, which do not confirm to the above requirements. All such costs associated with the incorrect supply of containers shall be for the account of the shipping line and/or supplying depot.